


FEATURES:

- ✓ Architectural luminaire with direct/indirect lighting distribution.
- ✓ Light source: Nano-Lit LED Strips.
- ✓ Diffused illumination is provided by two opal frosted polycarbonate round domes.
- ✓ Suitable for non-insulated recessed ceiling for T-bar or drywall.
- ✓ Fixture body is made from light weight steel in white finish.
- ✓ Proprietary Nano-Lit Quantum Dot Technology >90CRI.
- ✓ Has a proven record in office, commercial and retail applications.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED MLT+ SOURCE — VOLTAGE — DRIVER — MOUNTING — FINISH — CCT

Enter the Product Code into the boxes above.

SOURCE

-
- 50W LED

VOLTAGE

-
- 120V
-
-
- 277V
-
-
- 347V*

* Not available for all configurations.

DRIVER

-
- BT - Nano-Lit Bluetooth

MOUNTING

-
- RS - Recessed
-
-
- DW - Dry Wall

FINISH


-
- WH - White

CCT

-
- CR - Circadian Rythm

DIMENSIONS:

Length	Width	Height
23.75"	23.75"	3.0"


LUMEN OUTPUT W/Ft:

Watts	2700K-6500k
50 W	Avg. 5107.5 lm

Project:

Type: